

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau





(43) International Publication Date  
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number  
**WO 2004/007619 A1**

- (51) International Patent Classification<sup>7</sup>: **C09B 33/02**, 43/16, 62/09
- (21) International Application Number: PCT/GB2003/003056
- (22) International Filing Date: 14 July 2003 (14.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0216539.7 16 Jan 05 16 July 2002 (16.07.2002) GB
- (71) Applicant (for all designated States except US): **AVECIA LIMITED** [GB/GB]; Hexagon House, Blackley, Manchester M9 8ZS (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **O'SHAUGHNESSY, Helen, Ava** [GB/GB]; Hexagon House, P.O. Box 42, Blackley, Manchester M9 9ZS (GB); **HADJISOTERIOU, Maria, Soteri** [GB/GB]; Hexagon House, P.O. Box 42, Blackley, Manchester M9 8ZS (GB).
- (74) Agents: **MAYALL, John et al.**; Avecia Limited, Intellectual Property Group, P.O. Box 42, Hexagon House, Blackley, Manchester M9 8ZS (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **DISAZO DYES AND INK JET INKS CONTAINING THEM**



(57) Abstract: A compound of Formula (1) where in: A<sup>1</sup> and A<sup>2</sup> are each independently optionally substituted phenyl or naphthyl; each Q independently is optionally substituted phenylene; each R<sup>1</sup> independently is H or optionally substituted alkyl; R<sup>2</sup> is H or optionally substituted alkyl; and R<sup>3</sup> is alkyl carrying a sulpho group; provided that the compound of Formula (1) carries at least one carboxylic acid group; and provided the compound of Formula (1) is not of Formula (2): Formula (2) wherein: m is 1 or 2; n is 1 or 2; and x is 2 to 4. Also claimed are compositions and inks.

DISAZO DYES AND INK JET INKS CONTAINING THEM

This present invention relates to compounds and their salts, to compositions containing such compounds and their use in ink jet printing ("IJP"), to ink jet printer  
5 cartridges and to ink jet printing processes.

IJP is a non-impact printing technique in which droplets of coloured liquids are ejected through a fine nozzle onto a substrate without bringing the nozzle into contact with the substrate.

IJP is a relatively inexpensive way of printing multicolour images, for example  
10 pictures obtained from digital sources such as electronic cameras, scanners and the Internet. The use of ink jet printers to print colour images in the home or office environment is now becoming commonplace. However IJP has a big disadvantage compared to conventional silver halide photography in that the resultant images fade in ordinary daylight. Thus, there is a need to improve the light-fastness properties of prints  
15 to prevent images fading or vanishing, or becoming discoloured over time.

In addition, there are many demanding performance requirements for colorants and inks used in IJP. For example sharp, non-feathered images having good water-fastness and optical density are required. The inks are required to dry quickly when applied to a substrate to prevent smudging, but they should not form a crust over the tip  
20 of an ink jet nozzle which stops the printer from working effectively. The inks should also be stable to storage over time without decomposing by forming a precipitate which could block the fine nozzle. Ideally the inks should also possess good humidity and ozone fastness, have a high tinctorial strength and be bright.

The choice of a colorant in ink jet systems is critical to image quality and fastness.  
25 The colorants should also have a high degree of light-fastness after printing onto a substrate. For aqueous inks, the colorants need to be sufficiently soluble in water to prepare a solution that is capable of producing adequate density on the substrate and be stable for extended periods of storage without precipitation.


GB 2036780 describes certain yellow disazo dyes for the conventional dyeing of  
30 cellulose-containing materials. The dyes comprise two azo components linked by a 1,3,5-triazine (cyanuric) moiety, where one of the azo components is a disulpho-naphthyl group and the other comprises two phenyl groups.

US 5519121 discloses certain cyanuric-linked disazo dyestuffs in printing inks for textiles and paper where one terminal component of the molecule comprises a disulpho-naphthyl group and the other terminal component comprises a sulphonated phenyl group.  
35

EP 468647 discloses certain cyanuric-linked disazo yellow dyestuffs for use in inks where both terminal groups independently comprise phenyl or naphthyl, with the proviso that there is at least one carboxylic acid (or thiocarboxylic acid) on a terminal component.

Surprisingly it has been found that compounds of the present invention are excellent colorants for ink jet printing inks.

According to the present invention there is provided a compound of Formula (1):




Formula (1)

wherein:

- A<sup>1</sup> and A<sup>2</sup> are each independently optionally substituted phenyl or naphthyl;  
 each Q independently is optionally substituted phenylene;  
 each R<sup>1</sup> independently is H or optionally substituted alkyl;  
 R<sup>2</sup> is H or optionally substituted alkyl; and  
 R<sup>3</sup> is alkyl carrying a sulfo group;

provided that the compound of Formula (1) carries at least one carboxylic acid group; and  
 provided that the compound of Formula (1) is not a compound of Formula (2) or a salt thereof:



Formula (2)

wherein:

- m is 1 or 2;  
 n is 1 or 2; and  
 x is 2 to 4.

In one embodiment of the invention, A<sup>1</sup> and A<sup>2</sup> are the same as each other.

In a further embodiment of the invention, A<sup>1</sup> and A<sup>2</sup> are different from each other.

In a preferred embodiment, one of A<sup>1</sup> and A<sup>2</sup> is optionally substituted naphthyl and the other is optionally substituted phenyl.

In another preferred embodiment, one of A<sup>1</sup> and A<sup>2</sup> carries at least one carboxylic acid group and the other is free from carboxylic acid groups.

In compounds of Formula (2) m, n and x are preferably 2.

Preferred salts are alkali metal salts (especially lithium, sodium and potassium salts), ammonium and substituted ammonium salts and mixtures thereof. Especially preferred salts are sodium, potassium and lithium salts, salts with ammonia and volatile


amines and mixtures thereof. The lithium salts have good solubility, forming particularly storage stable inks with low toxicity and a low tendency to block ink jet nozzles.

The compounds may be converted into a desired salt using known techniques. For example, an alkali metal salt of a compound may be converted into the ammonium or substituted ammonia salt by dissolving an alkali metal salt of the compound in water, acidifying with a mineral acid and adjusting the pH of the solution to pH 9 to 9.5 with ammonia or the amine and removing the alkali metal cations by dialysis or by use of an ion exchange resin.

Examples of amines which may be used to form such salts include methylamine, dimethylamine, trimethylamine, ethylamine, n-propylamine, iso-propylamine, n-butylamine, iso-butylamine, sec-butylamine, tert-butylamine, piperidine, pyridine, morpholine, allylamine, diethylamine, triethylamine, tetramethylamine and mixtures thereof. It is not essential that the dyes are completely in the form of the ammonium salt or substituted ammonium salt and mixed alkali metal and either ammonium salt or substituted ammonium salt are effective, especially those in which at least 50% of the cations are ammonium or substituted ammonium ions.

The above compounds are preferably yellow dyes.

Compounds of Formula (1) may be prepared by condensing an amine of formula  $\text{HNR}^2\text{R}^3$  with a compound of the Formula (3):



Formula (3)

wherein:

X is a labile atom or group; and

$\text{A}^1$ ,  $\text{A}^2$ ,  $\text{R}^1$ ,  $\text{Q}$ ,  $\text{R}^2$  and  $\text{R}^3$  are as hereinbefore defined.

Preferably X is halo (especially Cl or F).

The condensation is preferably performed in an aqueous medium, more preferably in water. A pH above 7 is preferred because an alkaline pH removes any HX produced during the course of the condensation.

The condensation is preferably performed at a temperature of 5 to 110°C.

The compound of Formula (3) may be prepared by condensing one equivalent of s-triazine carrying three X groups (e.g. cyanuric chloride) with two amines, one of which is of formula  $\text{A}^1\text{-N}=\text{N}-\text{Q}-\text{NHR}^1$  and the other of formula  $\text{A}^2\text{-N}=\text{N}-\text{Q}-\text{NHR}^1$ , wherein X,  $\text{A}^1$ ,  $\text{A}^2$ ,  $\text{Q}$  and  $\text{R}^1$  are as hereinbefore defined. Preferred condensation considerations are as described above.

The amines of formula  $A^1-N=N-Q-NHR^1$  and  $A^2-N=N-Q-NHR^1$  may be prepared by diazotising amines of formula  $A^1-NH_2$  and  $A^2-NH_2$  respectively and coupling the resultant diazonium salt with compounds of formula  $H-Q-NHR^1$ , wherein  $A^1$ ,  $A^2$ ,  $Q$  and  $R^1$  are as hereinbefore defined. Typical diazotisation conditions are those usually employed in the  
5 dyestuff art, e.g. employing a temperature below  $5^\circ C$ , water, dilute mineral acid and sodium nitrate as diazotising agent.

Alternative methods of preparing compounds of Formula (1) may also be used. For example, the amine  $NHR^2R^3$  may be condensed with cyanuric chloride followed by condensation with the amine or amines of formula  $A^1-N=N-Q-NR^1H$  and  $A^2-N=N-Q-NR^1H$   
10 (wherein  $R^1$ ,  $R^2$ ,  $R^3$ ,  $Q$ ,  $A^1$  and  $A^2$  are as hereinbefore defined).

According to a second aspect of the present invention there is provided a composition comprising a compound according to the first aspect of the invention, or a salt thereof, and a liquid medium. The composition preferably comprises:

(a) from 0.01 to 30 parts of a compound of Formula (1), or salt thereof, as  
15 hereinbefore defined; and

(b) from 70 to 99.99 parts of a liquid medium;

wherein all parts are by weight and the number of parts of (a)+(b)=100.

Preferred liquid media include water or a mixture of water and one or more organic solvents.

20 When the liquid medium comprises a mixture of water and organic solvent, the weight ratio of water to organic solvent is preferably from 99:1 to 1:99, more preferably from 99:1 to 50:50 and especially from 95:5 to 80:20.

It is preferred that any organic solvent present in the mixture of water and organic solvent is water-miscible. Preferred water-miscible organic solvents include  $C_{1-6}$ -alkanols, preferably methanol, ethanol, n-propanol, isopropanol, n-butanol, sec-butanol, tert-butanol, n-pentanol, cyclopentanol and cyclohexanol; linear amides, preferably dimethylformamide or dimethylacetamide; ketones and ketone-alcohols, preferably acetone, methyl ether ketone, cyclohexanone and diacetone alcohol; water-miscible ethers, preferably tetrahydrofuran and dioxane; diols, preferably diols having from 2 to 12 carbon atoms, for example pentane-1,5-  
25 diol, ethylene glycol, propylene glycol, butylene glycol, pentylene glycol, hexylene glycol and thiodiglycol and oligo- and poly-alkyleneglycols, preferably diethylene glycol, triethylene glycol, polyethylene glycol and polypropylene glycol; triols, preferably glycerol and 1,2,6-hexanetriol; mono- $C_{1-4}$ -alkyl ethers of diols, preferably mono- $C_{1-4}$ -alkyl ethers of diols having 2 to 12 carbon atoms, especially 2-methoxyethanol, 2-(2-methoxyethoxy)ethanol, 2-(2-ethoxyethoxy)-ethanol, 2-[2-(2-methoxyethoxy)ethoxy]ethanol, 2-[2-(2-ethoxyethoxy)-  
30 ethoxy]-ethanol and ethyleneglycol monoallylether; cyclic amides, preferably 2-pyrrolidone, N-methyl-2-pyrrolidone, N-ethyl-2-pyrrolidone, caprolactam and 1,3-dimethylimidazolidone; cyclic esters, preferably caprolactone; sulphoxides, preferably dimethyl sulphoxide and

sulpholane. Preferably the liquid medium comprises water and 2 or more, especially from 2 to 8, water-soluble organic solvents.

Especially preferred water-miscible organic solvents are cyclic amides, especially 2-pyrrolidone, N-methyl-pyrrolidone and N-ethyl-pyrrolidone; diols, especially 1,5-pentane diol, ethyleneglycol, thiodiglycol, diethyleneglycol and triethyleneglycol; and mono- C<sub>1-4</sub>-alkyl and C<sub>1-4</sub>-alkyl ethers of diols, more preferably mono- C<sub>1-4</sub>-alkyl ethers of diols having 2 to 12 carbon atoms, especially 2-methoxy-2-ethoxy-2-ethoxyethanol.

The pH of the composition is preferably from 4 to 11, more preferably from 7 to 10.

The viscosity of the composition at 25°C is preferably less than 50cP, more preferably less than 20 cP and especially less than 5cP.

When the composition according to the invention is used as ink jet printing compositions, the composition preferably has a concentration of halide ions of less than 500 parts per million, more preferably less than 100 parts per million. It is especially preferred that the composition has less than 100, more preferably less than 50 parts per million of divalent and trivalent metals, wherein parts refer to parts by weight relative to the total weight of the composition. We have found that purifying the compositions to reduce the concentration of these undesirable ions reduces nozzle blockage in ink jet printing heads, particularly in thermal ink jet printers.

The compounds of Formula (1) may be used as the sole colorant in the compositions because of their attractive yellow shade. However, if desired, one may combine the present compounds with one or more further yellow colorants if a slightly different shade is required for a particular end use. The further colorants are preferably dyes. When further colorants are included in the composition these are preferably selected from but not limited to yellow colorants such as C.I.Direct Yellow 142; C.I.Direct Yellow 132; C.I.Direct Yellow 86; C.I.Direct Yellow 85; C.I. Direct Yellow 173; and C.I.Acid Yellow 23 and combinations thereof.

The composition according to this aspect of the present invention may also contain additional components conventionally used in ink jet printing inks, for example viscosity and surface tension modifiers, corrosion inhibitors, biocides, kogation reducing additives and surfactants which may be ionic or non-ionic.

A third aspect of the present invention provides a process for printing an image on a substrate comprising applying thereto a composition according to the second aspect of the present invention.

The process for printing the image preferably is carried out by means of an ink jet printer. The ink jet printer preferably applies the composition to the substrate in the form of droplets which are ejected through a small orifice onto the substrate. Preferred ink jet printers are piezoelectric ink jet printers and thermal ink jet printers. In thermal ink jet printers, programmed pulses of heat are applied to the composition in a reservoir by means of a resistor adjacent to the orifice, thereby causing the composition to be ejected in the

form of small droplets directed towards the substrate during relative movement between the substrate and the orifice. In piezoelectric ink jet printers the oscillation of a small crystal causes ejection of the composition from the orifice.

The substrate is preferably paper, plastic, a textile, metal or glass, more preferably paper, an overhead projector slide or a textile material, especially paper.

Preferred papers are plain or treated papers which may have an acid, alkaline or neutral character. Examples of commercially available treated papers include HP Premium Coated Paper, HP Photopaper™ (both available from Hewlett Packard Inc.); Stylus™ Pro 720 dpi Coated Paper, Epson Photo Quality™ Glossy Film, Epson Photo Quality™ Glossy Paper (all available from Seiko Epson Corp.); Canon HR 101 High Resolution™ Paper, Canon GP 201 Glossy™ Paper, Canon HG 101 and HG201 High Gloss™ Film, Canon PR101 (all available from Canon); Kodak Premium™ Photopaper, Kodak Premium™ InkJetpaper (available from Kodak); Konica Inkjet Paper QP™ Professional Photo Glossy, Konica Inkjet Paper QP™ Professional Photo 2-sided Glossy, Konica Inkjet Paper QP™ Premium Photo Glossy, Konica Inkjet Paper QP™ Premium Photo Silky (available from Konica).

A fourth aspect of the present invention provides an ink jet printer cartridge, optionally refillable, comprising one or more chambers and a composition, wherein the composition is present in at least one of the chambers and the composition is as defined in the second aspect of the invention.


A fifth aspect of the present invention provides separately a paper, an overhead projector slide or a textile material printed with a composition according to the present invention or by means of a process according to the third aspect of the present invention.

The invention is further illustrated by the following Examples in which all parts and percentages are by weight unless otherwise stated.

## EXAMPLES

### Example 1

#### 5 Preparation of Dye 1:



Dye 1

#### 10 Stage (1) Preparation of Monoazo(1).

3-sulpho-aniline (17.3g) was dissolved in water (400ml) at neutral pH, sodium nitrite (6.9g) was added and the mixture was cooled to 0-5° C. Concentrated hydrochloric acid (30ml) was added, and the mixture was stirred until diazotisation was complete. Excess nitrous acid was destroyed with sulphamic acid, and a solution of o-anisidine- $\omega$ -methanesulphonic acid (OAMS) (32g), dissolved in water (300 ml) at neutral pH, was added to the diazonium salt solution. The pH was increased 7 with sodium carbonate, and the reaction mixture was stirred overnight at room temperature. The resultant precipitate was filtered off and the filter cake was resuspended in water (800ml), sodium hydroxide solution (20 ml) was added, and the mixture was heated to 60°C. When reaction was complete the mixture was cooled to room temperature, the pH was adjusted to pH 4 and sodium chloride solution (10% w/v) was added to precipitate the product ("Monoazo(1)") which was isolated by filtration.

#### 25 Stage (2) Preparation of Monoazo(2).

5-amino-isophthalic acid (18g) was dissolved in water (200ml), and the pH was adjusted to pH7 with sodium hydroxide. Sodium nitrite (6.9g) was added and the mixture was stirred for 5 minutes, then cooled to 0-5° C. Concentrated HCl (35ml) was added slowly, and stirring continued at 0-5°C until diazotisation was complete. Excess nitrous acid was destroyed with sulphamic acid. A solution of aniline- $\omega$ -methanesulphonic acid (AMS) (32g) in water (300 ml) at neutral pH was added to the diazonium salt solution, and the



pH was increased to pH7 with sodium carbonate. The mixture was stirred overnight at room temperature, whereupon the precipitated product was filtered off, and resuspended in water (800ml), and the pH adjusted to pH10 with sodium hydroxide. The mixture was heated mixture to 60-70°C, and when hydrolysis was complete cooled to room temperature, whereupon the pH was adjusted to pH4. A solution of sodium chloride (10% w/v) was added to precipitate the product ("Monoazo(2)") which was isolated by filtration.

### Stage (3) Preparation of Title Dye

Monoazo(1) (0.2mol) was dissolved in water at pH7, calsolene oil (2drops) was added and the solution was cooled to 0-5° C. Cyanuric chloride (4g) added over 10 minutes, during which time the pH was maintained pH 6.5-7 with sodium carbonate solution. The mixture was stirred until reaction was complete, then allowed to warm to room temperature. The pH was adjusted pH7 and the mixture was stirred 1 hour.

A solution of Monoazo(2) (0.2mol) in water (100ml) was added to the above solution, and the pH was maintained at pH7 for 24 hours. When reaction was complete the pH was lowered to pH4 and sodium chloride (20%w/v) was added to precipitate the product, which was isolated by filtration and washed with saturated brine solution. The solid was resuspended in water (500ml) and 2-aminoethanesulphonic acid (0.6mol) was added. The pH was adjusted to pH 9.5 and the mixture heated to 70° C for 6 hours, and subsequently cooled to room temperature and adjusted to pH3 whereupon the product precipitated completely out of solution and was isolated by filtration. The solution was then dialysed using Visking™ tubing (<50  $\mu\text{Scm}^{-1}$ ) to low conductivity, screened through a cascade of filters (GF/A, GF/D, 0.45  $\mu\text{m}$ ) and dried in the oven to give the title product.

### Examples 2 to 10

The method of Example 1 was repeated, except that in place of 3-sulfoaniline in Stage (1) there was used the amine indicated in column A<sup>1</sup> of Table 1, in place of OAMS in Stage (1) there was used the compound indicated in column Q<sup>1</sup> of Table 1, and in place of AMS in Stage (2) there was used the compound indicated in column Q<sup>2</sup> of Table (1), wherein the compounds in columns Q<sup>1</sup> and Q<sup>2</sup> are as defined below:

OAMS = o-anisidine- $\omega$ -methanesulphonate

MAMS = m-anisidine- $\omega$ -methanesulphonate

AMS = aniline- $\omega$ -methanesulphonate

MT = m-toluidine









MEA = m-ethylaniline.

In Example 2 only, 2-(methylamino)ethane sulphonic acid was used in place of 2-aminoethane sulphonic acid in Stage (3).

The resultant dye structure in each case is shown in the far right hand column of Table 1.

Table 1

Example Number	A <sup>1</sup>	Q <sup>1</sup>	Q <sup>2</sup>	Final structure
2		AMS	AMS	
3		MAMS	MT	
4		MAMS	MT	
5		OAMS	MT	
6		MEA	MT	

7		MT	MT	MT	
8		MAMS	MEA	MT	
9		MT	AMS	AMS	
10		MAMS	AMS	AMS	

Example 11 - Ink formulations and testing

Ink jet printing inks were prepared according to the following formulation wherein Dye was the dye from Examples 1 to 10 above:

	2-Pyrrolidone	5 parts
5	Thiodiglycol	5 parts
	Surfynol™ 465	1 part (from Air Products Inc., USA)
	Dye	3 parts
	Water	86 parts.

10 The inks containing Dyes 1 to 10 ("Inks 1 to 10") were printed onto a range of proprietary media using an Epson Stylus™ 880 piezoelectric ink jet printer, and gave prints of excellent light and ozone fastness.

Further inks may be prepared in a similar fashion according to the formulations shown in Tables (I) and (II) wherein the dye described in the first column is the dye made in the above examples, and wherein numbers quoted in the second column onwards refer to the number of parts of the relevant ingredient and all parts are by weight. The inks may be applied to paper by thermal or piezo ink jet printing.

The following abbreviations are used in Table (I) and (II):

	PG = propylene glycol
	DEG = diethylene glycol
20	NMP = N-methyl pyrrolidone
	DMK = dimethylketone
	IPA = isopropanol
	MEOH = methanol
	2P = 2-pyrrolidone
25	MIBK = methylisobutyl ketone
	P12 = propane-1,2-diol
	BDL = butane-2,3-diol
	CET= cetyl ammonium bromide
	PHO = Na <sub>2</sub> HPO <sub>4</sub> and
30	TBT = tertiary butanol
	TDG = thiodiglycol

TABLE I


Dye	Dye Content	Water	PG	DEG	NMP	DMK	NaOH	Na Stearate	IPA	MEOH	2P	MIBK
1	2.0	80	5		6	4					5	
2	3.0	90		5	5		0.2			5	1	
3	10.0	85	3		3	3						1
4	2.1	91		8								5
5	3.1	86	5					0.2	4			
6	1.1	81			9		0.5	0.5	6		9	
7	2.5	60	4	15	3	3			10	10	5	4
8	5	65		20		5						
9	2.4	75	5	4						6		5
10	4.1	80	3	5	2	10		0.3				
1	3.2	65		5	4	6			5	4	6	5
2	5.1	96								4		
3	10.8	90	5						5			
4	10.0	80	2	6	2	5			1		4	
5	1.8	80		5							15	
6	2.6	84			11						5	
7	3.3	80	2			10				2		6
8	12.0	90				7	0.3		3			
9	5.4	69	2	20	2	1					3	3
10	6.0	91			4						5	

TABLE II

Dye	Dye Content	Water	PG	DEG	NMP	CET	TBT	TDG	BDL	PHO	2P	PI2
1	3.0	80	15			0.2					5	
2	9.0	90		5						1.2		5
3	1.5	85	5	5		0.15	5.0	0.2		0.12		
4	2.5	90		6	4							6
5	3.1	82	4	8		0.3						
6	0.9	85		10					5	0.2		
7	8.0	90		5	5			0.3				
8	4.0	70		10	4				1		4	11
9	2.2	75	4	10	3				2		6	
10	10.0	91			6						3	
1	9.0	76		9	7		3.0			0.95	5	
2	5.0	78	5	11							6	
3	5.4	86			7						7	
4	2.1	70	5	5	5	0.1	0.2	0.1	5	0.1	5	
5	2.0	90		10								
6	2	88						10				
7	5	78			5			12			5	
8	8	70	2		8			15			5	
9	10	80						8			12	
10	10	80		10								

CLAIMS

1. A compound of Formula (1):




Formula (1)

wherein:

- A<sup>1</sup> and A<sup>2</sup> are each independently optionally substituted phenyl or naphthyl;  
 each Q independently is optionally substituted phenylene;  
 each R<sup>1</sup> independently is H or optionally substituted alkyl;  
 R<sup>2</sup> is H or optionally substituted alkyl; and  
 R<sup>3</sup> is alkyl carrying a sulpho group;

provided that the compound of Formula (1) carries at least one carboxylic acid group; and  
 provided the compound of Formula (1) is not a compound of Formula (2) or a salt thereof:



Formula (2)

wherein:

- m is 1 or 2;  
 n is 1 or 2; and  
 x is 2 to 4.

2. A compound according to claim 1 wherein A<sup>1</sup> and A<sup>2</sup> are different to each other.

3. A compound according to either claim 1 or claim 2 wherein one of A<sup>1</sup> and A<sup>2</sup> carries at least one carboxylic acid group and the other is free from carboxylic acid groups.

4. A compound according to Claim 1 wherein A<sup>1</sup> and A<sup>2</sup> are the same as each other.

5. A composition comprising a compound of Formula (1) as defined in any of claims 1 to 4 and a liquid medium.
- 5 6. A process for printing an image on a substrate comprising applying thereto a composition according to claim 5.
- 10 7. An ink jet printer cartridge, optionally refillable, comprising one or more chambers and a composition, wherein the composition is present in at least one of the chambers and the composition is as defined in claim 5.
8. An paper, an overhead projector slide or a textile material printed with a composition according to claim 5 or by means of a process according to claim 6.



## INTERNATIONAL SEARCH REPORT

PCT/GB 03/03056

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C09B33/02 C09B43/16 C09B62/09

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C09B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, CHEM ABS Data, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 036 780 A (BAYER AG) 2 July 1980 (1980-07-02) cited in the application claim 1	1-8
A	US 5 519 121 A (HASSEN RUECK KARIN ET AL) 21 May 1996 (1996-05-21) cited in the application claim 1	1-8

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

20 October 2003

Date of mailing of the international search report

31/10/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Wolf, C

# INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/GB 03/03056

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2036780	A	02-07-1980	DE 2851787 A1	12-06-1980
			BR 7907757 A	22-07-1980
			FR 2442873 A1	27-06-1980
			JP 1445407 C	30-06-1988
			JP 55078059 A	12-06-1980
			JP 62052784 B	06-11-1987
US 5519121	A	21-05-1996	DE 4406950 A1	07-09-1995
			DE 59503964 D1	26-11-1998
			EP 0671441 A2	13-09-1995
			JP 7258564 A	09-10-1995